

AIR HOSE / COUPLERS



3536
 For Use with 3538, 3539
 ColorConnex Green Coupler
 Type B, 1/4 in FNPT
 Steel/Aluminum
 Max Pressure: 300 psi
 Box Qty. 1



3537
 For Use with 3538, 3539
 ColorConnex Green Coupler
 Type B, 1/4 in MNPT
 Steel/Aluminum
 Max Pressure: 300 psi
 Box Qty. 1



3538
 For Use with 3536, 3537
 ColorConnex Green Plug
 Type B, 1/4 in FNPT
 6061-T6 Aircraft Aluminum
 Max Pressure: 300 psi
 Box Qty. 1



3539
 For Use with 3536, 3537
 ColorConnex Green Plug
 Type B, 1/4 in MNPT
 6061-T6 Aircraft Aluminum
 Max Pressure: 300 psi
 Box Qty. 1



3541
 For Use with 3543, 3544
 ColorConnex Blue Coupler
 Type C, 1/4 in FNPT
 Steel/Aluminum
 Max Pressure: 300 psi
 Box Qty. 1



3542
 For Use with 3543, 3544
 ColorConnex Blue Coupler
 Type C, 1/4 in MNPT
 Steel/Aluminum
 Max Pressure: 300 psi
 Box Qty. 1



3543
 For Use with 3541, 3542
 ColorConnex Blue Plug
 Type C, 1/4 in FNPT
 6061-T6 Aircraft Aluminum
 Max Pressure: 300 psi
 Box Qty. 1



3544
 For Use with 3541, 3542
 ColorConnex Blue Plug
 Type C, 1/4 in MNPT
 6061-T6 Aircraft Aluminum
 Max Pressure: 300 psi
 Box Qty. 1



3551
 For Use with 3553, 3554
 ColorConnex Red Coupler
 Type D, 1/4 in FNPT
 Steel/Aluminum
 Max Pressure: 300 psi
 Box Qty. 1



3552
 For Use with 3553, 3554
 ColorConnex Red Coupler
 Type D, 1/4 in MNPT
 Steel/Aluminum
 Max Pressure: 300 psi
 Box Qty. 1



3553
 For Use with 3551, 3552
 ColorConnex Red Plug
 Type D, 1/4 in FNPT
 6061-T6 Aircraft Aluminum
 Max Pressure: 300 psi
 Box Qty. 1



3554
 For Use with 3551, 3552
 ColorConnex Red Plug
 Type D, 1/4 in MNPT
 6061-T6 Aircraft Aluminum
 Max Pressure: 300 psi
 Box Qty. 1



3556
 For Use with 3558, 3587, 3588
 Flexzilla High Flow Coupler
 1/4 in. MNPT
 Steel/Aluminum
 Max Pressure: 300 psi
 Box Qty. 1



3558
 For Use with 3556, 3586
 Flexzilla High Flow
 Ball Swivel Plug
 1/4 in. MNPT
 Nickel Plated Steel
 Max Pressure: 300 psi
 Box Qty. 1



3566
 H Style Coupler
 3/8 in. FNPT
 With Buna-N seal
 Max Pressure: 300 psi
 Box Qty. 1



3567
 H Style Plug
 1/4 in. MNPT
 Max Pressure: 300 psi
 Box Qty. 1

AIR HOSE / COUPLERS



FLEXZILLA® PRO HIGH FLOW INTERCHANGE


FLEXZILLA® Pro High Flow couplers and plugs allows Twice The Flow to your air tools. Connect Flexzilla High Flow fittings from your tool all the way to the compressor. This ensures the best performance your air system can provide. For maximum efficiency, use Flexzilla Pro High Flow! Maximum Torque - Maximum RPM - Push Connect System. Maximum Working Pressure: 300 PSI

- | | | |
|-------------|---|------------|
| 3585 | High Flow Kit Includes (1) 3586, (1) 3587, (1) 3588 | Box Qty. 1 |
| 3586 | High Flow Coupler 1/4" FNPT | Box Qty. 1 |
| 3587 | High Flow Plug 1/4" FNPT | Box Qty. 1 |
| 3588 | High Flow Plug 1/4" MNPT | Box Qty. 1 |

AIR HOSE COUPLERS

(Coupler/Plug drawings are not actual size)

- Precision engineered for maximum performance.....longer life!
- Tougher wear resistant, anti-corrosion materials throughout.
- They swivel to prevent air line kinks! • Fully automatic. • Permits 45 cfm air flow at 100 p.s.i.g.
- Operating pressure up to 250 p.s.i.g. • Operating temperature range: -40½ F. To +250½ F.



3550

Coupler
1/4" Female NPT
Mates with #3555 & #3560
B = 1-1/16"
C = 1-31/32"
Box Qty. 1



3555

Male Nipple
1/4" NPT
Mates with #3550
B = 9/16"
C = 1-11/16"
Box Qty. 1



3560

Female Nipple
1/4" NPT
Mates with 3550
B = 5/8"
C = 1-3/4"
Box Qty. 1



3535

Coupler
1/4" Female NPT
Mates with #3540 & #3545
B = 1-1/16"
C = 1-11/16"
Box Qty. 1



3540

Male Nipple
1/4" NPT
Mates with #3535
B = 9/16"
C = 1-25/32"
Box Qty. 1



3545

Female Nipple
1/4" NPT
Mates with #3535
B = 5/8"
C = 1-9/16"
Box Qty. 1



3565

Coupler
1/4" Female NPT
Mates with #3570 & #3572
B = 1-1/16"
C = 2-13/32"
Box Qty. 1



3570

Male Nipple
1/4" NPT
Mates with #3565
B = 9/16"
C = 2-5/32"
Box Qty. 1



3572

Female Nipple
1/4" NPT
Mates with #3565
B = 5/8"
C = 2-1/16"
Box Qty. 1



AIR HOSE / COUPLERS



HVLV EURO Coupler & Plugs

To achieve optimum atomization, an HVLV Spray Gun requires sufficient air transfer through the gun to produce the necessary air pressure at the air cap and attain the proper CFM (cubic feet per minute). This is accomplished by using the new quick converting HVLV EURO Coupler that provides a larger inside diameter enabling more CFM to pass through the connection. The design of this system also enables complete insertion of the plug into the coupler before air is activated thus eliminating air pressure resistance during the plug connection.

- 3591** 1/4" Quick Converting Coupler - Female, NPT 1 Per Pkg.
- 3592** 1/4" Plug - Female, NPT 1 Per Pkg.
- 3593** 1/4" Plug - Male, NPT 1 Per Pkg.
- 3590** Coupler Set Contains: 1 - #3592, 1 - #3591 1 Set Per Pkg.



UNIVERSAL BRASS COUPLER

A coupler to fit all your needs! 1/4" Female Universal coupler that fits most ARO, MILTON, TOMCO, TRU-FLATE and INDUSTRIAL INTERCHANGE type mating nipples. Brass Body, NBR seal, Stainless Steel spring, Steel locking balls. Maximum operating pressure up to 220 psi. *Mates with #3540, #3545, #3555, #3560 above, but NOT #3570 and #3572.*

- 3595** 1/4" NPT Female Universal Brass Coupler 1 Per Pkg.

PUSH BUTTON SAFETY COUPLERS

Reduces the risk of possible injury due to accidental air line disconnect.

Double click to engage properly. First click locks coupler and plug; the second click engages the air pressure. To disconnect push button twice. First push relieves air pressure; second push allows plug and coupler to be disengaged.

- Max. Inlet Pressure:* 225 psi
- Max. Temperature:* -60°F to 140°F
- Air Flow:* 36 SCFM @ 90 psi
- Coupler Body Shell Material:* Fiberglass filled nylon 66
- Rubber Seal:* NBR 80



- 3535SC**
- Mates with #3540, #3545*
- 1/4" Female
- M Style Safety Coupler
- Box Qty. 1



- 3550SC**
- Mates with #3555, #3560*
- 1/4" Female
- A Style Safety Coupler
- Box Qty. 1



REPAIR FITTINGS FOR AIR HOSE

A 3/8" MPT Reusable Hose Coupling. Use on 3/8" rubber/wire braided hose. Reverse thread female section onto your hose, thread male section into female to secure coupling to hose. You can connect the hose coupling directly to a variety of female threaded guns, sockets, or swivels. Adapt and repair hoses in the field. Extend the life of damaged hoses. Easy to repair. No crimps required.

- Prod No. **3596** 3/8" ID x 5/8" OD (two-piece stem/ferrule) 1 per box
- Prod No. **3597** 3/8" ID x 3/4" OD (two-piece stem/ferrule) 1 per box

AIR HOSE / COUPLERS



3573
 Brass
 Hose Splicer
 For 3/8" I.D. Air Hose
 Barbed Type
 Box Qty. 10

3574
 Brass
 Hose Splicer
 For 1/4" I.D. Air Hose
 Barbed Type
 Box Qty. 10



3580
 Safety blow gun.
 Meets all federal standards relating to OSHA.
 Maximum inlet pressure 150 P.S.I.
 Inlet size 1/4" NPT.
 Box Qty. 1

35 Air Hose / Couplers

The Cyclone Blow Gun

The **Cyclone Blow Gun** features an ergonomically superior gun body for maximum comfort and control which reduces operator fatigue. A variable flow trigger regulates air flow precisely. The Cyclone delivers maximum flow, equal to or greater than the competition. The durable gun body is ideal for extreme use. Unique to the Cyclone is the modular accessory system, allowing you to customize the gun extension length and tips for a given application. Cyclone meets or exceeds OSHA standards.

3571
 Cyclone Blow Gun Kit
 Includes: (2) 6" Extensions
 (3) Needle Tips (1 in., 2 in., 3 in.)
 Xtreme-Flo Nozzle
 Quiet-Flo Nozzle
 Rubber Tip
 Tip Adapter
 Box Qty. 1



Flexzilla Enclosed Air Hose Reel Economical

FEATURES:

Auto Retract/Latch Hose Mechanism - Simplifies every job by keeping excess hose out of the work space.

Positive Latching Mechanism - Locks hose automatically in 18 in. intervals.

Durable Construction - Made from durable UV stabilized polypropylene.

Adjustable Hose Stopper - Increase or decrease the length of the hose that remains when hose is fully retracted.

Lead-in Hose Included - 3/8" x 3 ft. 1/4 in. MNPT

Swivel Mount Bracket - Pivots in the direction of your work, reel can be mounted to wall or ceiling.

Flexzilla Models - Includes Flexzilla air hose and lead-in hose.

Bend Restrictor - Prolongs the life of the air hose, featured on ZillaReel models.



4087
 Flexzilla Enclosed Air Hose Reel Economical, retractable.
 Includes 3/8" x 50 ft hose and Lead-in hose.
 Box Qty. 1

Flexzilla Retractable Air Hose Reel with Levelwind Technology

FEATURES:

- Adjustable Hose Stopper** - Increase or decrease the length of the hose that remains when hose is fully retracted.
- Seven Position Locking Bracket** - Reel can swivel freely on a mounting bracket up to 135° or can be locked into place using the locking brace. Up to seven different locking angles can be utilized.
- Latching Mode Switch** - Choose from latching hose every 3 ft. for extended use or switch to free run for immediate automatic rewinding.
- Extra Large Swivel** - A 3/4" swivel reduces flow restrictions and allows for maximum flow.
- Free Standing Base w/Built-in Handle** - Portable! Use freestanding or mounted on wall or ceiling. Flat base allows reel to rest on ground.
- Durable Construction** - Made from durable UV stabilized polypropylene.
- Lead-in Hose Included** - 3/8" x 5 ft. 1/4 in. MNPT
- Flexzilla Models** - Includes Flexzilla air hose and lead-in hose.

4088

Flexzilla Retractable Air Hose Reel

With Levelwind technology - a unique winding system that automatically layers hose back and forth across the reel ensuring that the hose is coiled smoothly and easily every time. Includes 3/8" x 75 ft. hose & 3/8" x 5 ft. Lead-in hose.
Box Qty. 1



"FLEXZILLA®" PRO (REPAIRABLE) AIR HOSE

"FLEXZILLA®" is a revolutionary hose featuring a Premium Hybrid Polymer material that redefines flexibility. Flexzilla® hose characteristics offer zero memory allowing it to lay-flat exactly where you drop it and will not work against you during operation or coiling after use. Extreme all-weather flexibility, even in subzero conditions (-40° to 140°F). Permits use in environments where general purpose PVC and rubber hoses may become too stiff. Kink resistant under pressure. Excellent abrasion-resistant outer cover. Includes bend restrictor that reduces wear and tear, prolonging the life of the hose. Flexzilla® Hi-Vis color, safety green, makes hose more visible in the workplace. This hose is field repairable with reusable aircraft aluminum fittings.



Maximum Working Pressure..... 300 PSI

Product No.	I.D.	Length	Fittings
4080	3/8"	25 Ft.	1/4" MNPT
4081	3/8"	35 Ft.	1/4" MNPT
4082	3/8"	50 Ft.	1/4" MNPT

AIR HOSE / COUPLERS

35 Air Hose / Couplers

"FLEXZILLA®" PRO WATER HOSE

FLEXZILLA® is a revolutionary hose featuring a Premium Hybrid Polymer material that redefines flexibility. Flexzilla® hose characteristics offer zero memory allowing it to lay-flat exactly where you drop it and will not work against you during operation or coiling after use. Extreme all-weather flexibility. Kink resistant under pressure. Excellent abrasion-resistant outer cover. Flexzilla® Hi-Vis color, safety green, makes hose more visible in the workplace. Includes bend restrictors that reduces wear and tear, prolonging the life of the hose. Anodized aircraft aluminum ends. Drinking water safe! This hose is field repairable!
Maximum Working Pressure: 150 PSI



4070
5/8" x 50 ft.
Flexzilla Garden Hose
Box Qty. 1

"BIG RED AIR HOSE"

"BIG RED" is an extremely flexible, durable hose for use with air, water or mild chemicals. It is resistant to oil and gasoline and with it's high flexibility you have an ideal hose for lube and repair bays. Both the inner hose and cover are made of Prime PVC, and cord-reinforced for added strength. Big Red is far more resistant to oil and gasoline than rubber, and offers three times the life under normal conditions. It is more flexible and weighs only half as much as comparable rubber hose.



Maximum Working Pressure..... 300 PSI
Burst Pressure..... 1200 PSI

Product No.	I.D.	Length	Fittings
4099	3/8"	35 Ft.	1/4" NPT



4084
Reusable End
Used With 3/8" Flexzilla Pro
Box Qty. 1



4085
Reusable Splicer
Used With 3/8" Flexzilla Pro
Box Qty. 1



4086
1/4" NPT
Swivel Connector
Bx. Qty. 1



9710 DeVilbiss 3 Stage Desiccant Filter/Dryer **Box Qty. 1**
9711 Replacement Filter Cartridges **Box Qty. 1**

Cost effective. Use anywhere. Complete air control. A perfect solution for restoration shops, customizing shops and hobbyist. High performance filtration with only 2 PSI pressure drop. Three-stage filtering with 0.1 micron rating produces clean, oil and humidity free air resulting in outstanding paint finishes by removing water particulates, oil and humidity. Quick change filter cartridge is easy to maintain. Bowl removal tool included. Larger filter media and longer life desiccant than disposable dryers: 4X more filter area, 16X more desiccant. Low life-cycle costs. Complete air control enabling better color match and coating thickness. Inlet shut off valve, regulator and gauge, humidity indicator, bowl drain.