

# AIR HOSE / COUPLERS



**3536**

For Use with 3538, 3539  
ColorConnex Green Coupler  
Type B, 1/4 in FNPT  
Steel/Aluminum  
Max Pressure: 300 psi  
Box Qty. 1



**3537**

For Use with 3538, 3539  
ColorConnex Green Coupler  
Type B, 1/4 in MNPT  
Steel/Aluminum  
Max Pressure: 300 psi  
Box Qty. 1



**3538**

For Use with 3536, 3537  
ColorConnex Green Plug  
Type B, 1/4 in FNPT  
6061-T6 Aircraft Aluminum  
Max Pressure: 300 psi  
Box Qty. 1



**3539**

For Use with 3536, 3537  
ColorConnex Green Plug  
Type B, 1/4 in MNPT  
6061-T6 Aircraft Aluminum  
Max Pressure: 300 psi  
Box Qty. 1



**3541**

For Use with 3543, 3544  
ColorConnex Blue Coupler  
Type C, 1/4 in FNPT  
Steel/Aluminum  
Max Pressure: 300 psi  
Box Qty. 1



**3542**

For Use with 3543, 3544  
ColorConnex Blue Coupler  
Type C, 1/4 in MNPT  
Steel/Aluminum  
Max Pressure: 300 psi  
Box Qty. 1



**3543**

For Use with 3541, 3542  
ColorConnex Blue Plug  
Type C, 1/4 in FNPT  
6061-T6 Aircraft Aluminum  
Max Pressure: 300 psi  
Box Qty. 1



**3544**

For Use with 3541, 3542  
ColorConnex Blue Plug  
Type C, 1/4 in MNPT  
6061-T6 Aircraft Aluminum  
Max Pressure: 300 psi  
Box Qty. 1



**3551**

For Use with 3553, 3554  
ColorConnex Red Coupler  
Type D, 1/4 in FNPT  
Steel/Aluminum  
Max Pressure: 300 psi  
Box Qty. 1



**3552**

For Use with 3553, 3554  
ColorConnex Red Coupler  
Type D, 1/4 in MNPT  
Steel/Aluminum  
Max Pressure: 300 psi  
Box Qty. 1



**3553**

For Use with 3551, 3552  
ColorConnex Red Plug  
Type D, 1/4 in FNPT  
6061-T6 Aircraft Aluminum  
Max Pressure: 300 psi  
Box Qty. 1



**3554**

For Use with 3551, 3552  
ColorConnex Red Plug  
Type D, 1/4 in MNPT  
6061-T6 Aircraft Aluminum  
Max Pressure: 300 psi  
Box Qty. 1

# AIR HOSE / COUPLERS



**3556**  
 For Use with 3558, 3587, 3588  
 Flexzilla High Flow Coupler  
 1/4 in. MNPT  
 Steel/Aluminum  
 Max Pressure: 300 psi  
 Box Qty. 1



**3558**  
 For Use with 3556, 3586  
 Flexzilla High Flow  
 Ball Swivel Plug  
 1/4 in. MNPT  
 Nickel Plated Steel  
 Max Pressure: 300 psi  
 Box Qty. 1

## FLEXZILLA® PRO HIGH FLOW INTERCHANGE

FLEXZILLA® Pro High Flow couplers and plugs allows Twice The Flow to your air tools. Connect Flexzilla High Flow fittings from your tool all the way to the compressor. This ensures the best performance your air system can provide. For maximum efficiency, use Flexzilla Pro High Flow! Maximum Torque - Maximum RPM - Push Connect System. Maximum Working Pressure: 300 PSI



<b>3585</b>	High Flow Kit Includes (1) 3586, (1) 3587, (1) 3588	Box Qty. 1
<b>3586</b>	High Flow Coupler 1/4" FNPT	Box Qty. 1
<b>3587</b>	High Flow Plug 1/4" FNPT	Box Qty. 1
<b>3588</b>	High Flow Plug 1/4" MNPT	Box Qty. 1


35 Air Hose / Couplers

35

## AIR HOSE COUPLERS

(Coupler/Plug drawings are not actual size)

- Precision engineered for maximum performance.....*longer life!*
- Tougher wear resistant, anti-corrosion materials throughout.
- They swivel to prevent air line kinks! • Fully automatic. • Permits 45 cfm air flow at 100 p.s.i.g.
- Operating pressure up to 250 p.s.i.g. • Operating temperature range: -40½ F. To +250½ F.



**3550**

Coupler  
 1/4" Female NPT  
 Mates with #3555 & #3560  
 B = 1-1/16"  
 C = 1-31/32"  
 Box Qty. 1



**3555**

Male Nipple  
 1/4" NPT  
 Mates with #3550  
 B = 9/16"  
 C = 1-11/16"  
 Box Qty. 1



**3560**

Female Nipple  
 1/4" NPT  
 Mates with 3550  
 B = 5/8"  
 C = 1-3/4"  
 Box Qty. 1



**3535**

Coupler  
 1/4" Female NPT  
 Mates with #3540 & #3545  
 B = 1-1/16"  
 C = 1-11/16"  
 Box Qty. 1



**3540**

Male Nipple  
 1/4" NPT  
 Mates with #3535  
 B = 9/16"  
 C = 1-25/32"  
 Box Qty. 1



**3545**

Female Nipple  
 1/4" NPT  
 Mates with #3535  
 B = 5/8"  
 C = 1-9/16"  
 Box Qty. 1



**3565**

Coupler  
 1/4" Female NPT  
 Mates with #3570 & #3572  
 B = 1-1/16"  
 C = 2-13/32"  
 Box Qty. 1



**3570**

Male Nipple  
 1/4" NPT  
 Mates with #3565  
 B = 9/16"  
 C = 2-5/32"  
 Box Qty. 1



**3572**

Female Nipple  
 1/4" NPT  
 Mates with #3565  
 B = 5/8"  
 C = 2-1/16"  
 Box Qty. 1



# AIR HOSE / COUPLERS



## HVLPEURO Coupler & Plugs

To achieve optimum atomization, an HVLPEURO Spray Gun requires sufficient air transfer through the gun to produce the necessary air pressure at the air cap and attain the proper CFM (cubic feet per minute). This is accomplished by using the new quick converting HVLPEURO Coupler that provides a larger inside diameter enabling more CFM to pass through the connection. The design of this system also enables complete insertion of the plug into the coupler before air is activated thus eliminating air pressure resistance during the plug connection.

- 3591** 1/4" Quick Converting Coupler - Female, NPT 1 Per Pkg.
- 3592** 1/4" Plug - Female, NPT 1 Per Pkg.
- 3593** 1/4" Plug - Male, NPT 1 Per Pkg.
- 3590** Coupler Set Contains: 1 - #3592, 1 - #3591 1 Set Per Pkg.



## UNIVERSAL BRASS COUPLER

A coupler to fit all your needs! 1/4" Female Universal coupler that fits most ARO, MILTON, TOMCO, TRU-FLATE and INDUSTRIAL INTERCHANGE type mating nipples. Brass Body, NBR seal, Stainless Steel spring, Steel locking balls. Maximum operating pressure up to 220 psi. *Mates with #3540, #3545, #3555, #3560 above, but NOT #3570 and #3572.*

- 3595** 1/4" NPT Female Universal Brass Coupler 1 Per Pkg.

## PUSH BUTTON SAFETY COUPLERS

Reduces the risk of possible injury due to accidental air line disconnect.

Double click to engage properly. First click locks coupler and plug; the second click engages the air pressure. To disconnect push button twice. First push relieves air pressure; second push allows plug and coupler to be disengaged.

- Max. Inlet Pressure:* 225 psi
- Max. Temperature:* -60°F to 140°F
- Air Flow:* 36 SCFM @ 90 psi
- Coupler Body Shell Material:* Fiberglass filled nylon 66
- Rubber Seal:* NBR 80



- 3535SC**
- Mates with #3540, #3545*
- 1/4" Female
- M Style Safety Coupler
- Box Qty. 1



- 3550SC**
- Mates with #3555, #3560*
- 1/4" Female
- A Style Safety Coupler
- Box Qty. 1



## REPAIR FITTINGS FOR AIR HOSE

A 3/8" MPT Reusable Hose Coupling. Use on 3/8" rubber/wire braided hose. Reverse thread female section onto your hose, thread male section into female to secure coupling to hose. You can connect the hose coupling directly to a variety of female threaded guns, sockets, or swivels. Adapt and repair hoses in the field. Extend the life of damaged hoses. Easy to repair. No crimps required.

- Prod No. **3596** 3/8" ID x 5/8" OD (two-piece stem/ferrule) 1 per box
- Prod No. **3597** 3/8" ID x 3/4" OD (two-piece stem/ferrule) 1 per box

# AIR HOSE / COUPLERS



**3573**  
 Brass  
 Hose Splicer  
 For 3/8" I.D. Air Hose  
 Barbed Type  
 Box Qty. 10

**3574**  
 Brass  
 Hose Splicer  
 For 1/4" I.D. Air Hose  
 Barbed Type  
 Box Qty. 10



**3580**  
 Safety blow gun.  
 Meets all federal standards relating to OSHA.  
 Maximum inlet pressure 150 P.S.I.  
 Inlet size 1/4" NPT.  
 Box Qty. 1

35 Air Hose / Couplers

35

## The Cyclone Blow Gun

The **Cyclone Blow Gun** features an ergonomically superior gun body for maximum comfort and control which reduces operator fatigue. A variable flow trigger regulates air flow precisely. The Cyclone delivers maximum flow, equal to or greater than the competition. The durable gun body is ideal for extreme use. Unique to the Cyclone is the modular accessory system, allowing you to customize the gun extension length and tips for a given application. Cyclone meets or exceeds OSHA standards.

**3571**  
 Cyclone Blow Gun Kit  
 Includes: (2) 6" Extensions  
 (3) Needle Tips (1 in., 2 in., 3 in.)  
 Xtreme-Flo Nozzle  
 Quiet-Flo Nozzle  
 Rubber Tip  
 Tip Adapter  
 Box Qty. 1



## Flexzilla Enclosed Air Hose Reel Economical

### FEATURES:

**Auto Retract/Latch Hose Mechanism** - Simplifies every job by keeping excess hose out of the work space.

**Positive Latching Mechanism** - Locks hose automatically in 18 in. intervals.

**Durable Construction** - Made from durable UV stabilized polypropylene.

**Adjustable Hose Stopper** - Increase or decrease the length of the hose that remains when hose is fully retracted.

**Lead-in Hose Included** - 3/8" x 3 ft. 1/4 in. MNPT

**Swivel Mount Bracket** - Pivots in the direction of your work, reel can be mounted to wall or ceiling.

**Flexzilla Models** - Includes Flexzilla air hose and lead-in hose.

**Bend Restrictor** - Prolongs the life of the air hose, featured on ZillaReel models.



**4087**  
 Flexzilla Enclosed Air Hose Reel Economical, retractable.  
 Includes 3/8" x 50 ft hose and Lead-in hose.  
 Box Qty. 1

## Flexzilla Retractable Air Hose Reel with Levelwind Technology

**FEATURES:**

**Adjustable Hose Stopper** - Increase or decrease the length of the hose that remains when hose is fully retracted.

**Seven Position Locking Bracket** - Reel can swivel freely on a mounting bracket up to 135° or can be locked into place using the locking brace. Up to seven different locking angles can be utilized.

**Latching Mode Switch** - Choose from latching hose every 3 ft. for extended use or switch to free run for immediate automatic rewinding.

**Extra Large Swivel** - A 3/4" swivel reduces flow restrictions and allows for maximum flow.

**Free Standing Base w/Built-in Handle** - Portable! Use freestanding or mounted on wall or ceiling. Flat base allows reel to rest on ground.

**Durable Construction** - Made from durable UV stabilized polypropylene.

**Lead-in Hose Included** - 3/8" x 5 ft. 1/4 in. MNPT

**Flexzilla Models** - Includes Flexzilla air hose and lead-in hose.

### 4088

Flexzilla Retractable Air Hose Reel

With Levelwind technology - a unique winding system that automatically layers hose back and forth across the reel ensuring that the hose is coiled smoothly and easily every time. Includes 3/8" x 75 ft. hose & 3/8" x 5 ft. Lead-in hose.

Box Qty. 1



## "FLEXZILLA®" PRO (REPAIRABLE) AIR HOSE

"FLEXZILLA®" is a revolutionary hose featuring a Premium Hybrid Polymer material that redefines flexibility. Flexzilla® hose characteristics offer zero memory allowing it to lay-flat exactly where you drop it and will not work against you during operation or coiling after use. Extreme all-weather flexibility, even in subzero conditions (-40° to 140°F). Permits use in environments where general purpose PVC and rubber hoses may become too stiff. Kink resistant under pressure. Excellent abrasion-resistant outer cover. Includes bend restrictor that reduces wear and tear, prolonging the life of the hose. Flexzilla® Hi-Vis color, safety green, makes hose more visible in the workplace. This hose is field repairable with reusable aircraft aluminum fittings.



Maximum Working Pressure..... 300 PSI

Product No.	I.D.	Length	Fittings
<b>4080</b> .....	3/8"	x 25 Ft.	.....1/4" MNPT
<b>4081</b> .....	3/8"	x 35 Ft.	.....1/4" MNPT
<b>4082</b> .....	3/8"	x 50 Ft.	.....1/4" MNPT

# AIR HOSE / COUPLERS

35 Air Hose / Couplers

## "FLEXZILLA®" PRO WATER HOSE

FLEXZILLA® is a revolutionary hose featuring a Premium Hybrid Polymer material that redefines flexibility. Flexzilla® hose characteristics offer zero memory allowing it to lay-flat exactly where you drop it and will not work against you during operation or coiling after use. Extreme all-weather flexibility. Kink resistant under pressure. Excellent abrasion-resistant outer cover. Flexzilla® Hi-Vis color, safety green, makes hose more visible in the workplace. Includes bend restrictors that reduces wear and tear, prolonging the life of the hose. Anodized aircraft aluminum ends. Drinking water safe! This hose is field repairable!  
Maximum Working Pressure: 150 PSI



**4070**  
5/8" x 50 ft.  
Flexzilla Garden Hose  
Box Qty. 1

## "BIG RED AIR HOSE"

"**BIG RED**" is an extremely flexible, durable hose for use with air, water or mild chemicals. It is resistant to oil and gasoline and with it's high flexibility you have an ideal hose for lube and repair bays. Both the inner hose and cover are made of Prime PVC, and cord-reinforced for added strength. Big Red is far more resistant to oil and gasoline than rubber, and offers three times the life under normal conditions. It is more flexible and weighs only half as much as comparable rubber hose.



Maximum Working Pressure..... 300 PSI  
Burst Pressure.....1200 PSI

Product No.	I.D.	Length	Fittings
<b>4102</b> .....	3/8" x 25 Ft.	.....	1/4" NPT
<b>4099</b> .....	3/8" x 35 Ft.	.....	1/4" NPT
<b>4103</b> .....	3/8" x 50 Ft.	.....	1/4" NPT



**4084**  
Reusable End  
Used With 3/8" Flexzilla Pro  
Box Qty. 1



**4085**  
Reusable Splicer  
Used With 3/8" Flexzilla Pro  
Box Qty. 1



**4086**  
1/4" NPT  
Swivel Connector  
Bx. Qty. 1



**9710 DeVilbiss 3 Stage Desiccant Filter/Dryer**      **Box Qty. 1**  
**9711 Replacement Filter Cartridges**                      **Box Qty. 1**

Cost effective. Use anywhere. Complete air control. A perfect solution for restoration shops, customizing shops and hobbyist. High performance filtration with only 2 PSI pressure drop. Three-stage filtering with 0.1 micron rating produces clean, oil and humidity free air resulting in outstanding paint finishes by removing water particulates, oil and humidity. Quick change filter cartridge is easy to maintain. Bowl removal tool included. Larger filter media and longer life desiccant than disposable dryers: 4X more filter area, 16X more desiccant. Low life-cycle costs. Complete air control enabling better color match and coating thickness. Inlet shut off valve, regulator and gauge, humidity indicator, bowl drain.