

S & R FASTENER CO., INC.

| | | | |
|--|--|---|---|
|  <p>85260 410 Hardened Stainless Steel Black Zinc Plated 10-16 x 1" Phillips Pan Head Self Drilling Screw Box Qty. 100</p> |  <p>3536 <i>For Use with 3538, 3539</i> ColorConnex Green Coupler Type B, 1/4 in FNPT Steel/Aluminum Max Pressure: 300 psi Box Qty. 1</p> |  <p>3537 <i>For Use with 3538, 3539</i> ColorConnex Green Coupler Type B, 1/4 in MNPT Steel/Aluminum Max Pressure: 300 psi Box Qty. 1</p> |  <p>3538 <i>For Use with 3536, 3537</i> ColorConnex Green Plug Type B, 1/4 in FNPT 6061-T6 Aircraft Aluminum Max Pressure: 300 psi Box Qty. 1</p> |
|  <p>3539 <i>For Use with 3536, 3537</i> ColorConnex Green Plug Type B, 1/4 in MNPT 6061-T6 Aircraft Aluminum Max Pressure: 300 psi Box Qty. 1</p> |  <p>3541 <i>For Use with 3543, 3544</i> ColorConnex Blue Coupler Type C, 1/4 in FNPT Steel/Aluminum Max Pressure: 300 psi Box Qty. 1</p> |  <p>3542 <i>For Use with 3543, 3544</i> ColorConnex Blue Coupler Type C, 1/4 in MNPT Steel/Aluminum Max Pressure: 300 psi Box Qty. 1</p> |  <p>3543 <i>For Use with 3541, 3542</i> ColorConnex Blue Plug Type C, 1/4 in FNPT 6061-T6 Aircraft Aluminum Max Pressure: 300 psi Box Qty. 1</p> |
|  <p>3544 <i>For Use with 3541, 3542</i> ColorConnex Blue Plug Type C, 1/4 in MNPT 6061-T6 Aircraft Aluminum Max Pressure: 300 psi Box Qty. 1</p> |  <p>3551 <i>For Use with 3553, 3554</i> ColorConnex Red Coupler Type D, 1/4 in FNPT Steel/Aluminum Max Pressure: 300 psi Box Qty. 1</p> |  <p>3552 <i>For Use with 3553, 3554</i> ColorConnex Red Coupler Type D, 1/4 in MNPT Steel/Aluminum Max Pressure: 300 psi Box Qty. 1</p> |  <p>3553 <i>For Use with 3551, 3552</i> ColorConnex Red Plug Type D, 1/4 in FNPT 6061-T6 Aircraft Aluminum Max Pressure: 300 psi Box Qty. 1</p> |
|  <p>3554 <i>For Use with 3551, 3552</i> ColorConnex Red Plug Type D, 1/4 in MNPT 6061-T6 Aircraft Aluminum Max Pressure: 300 psi Box Qty. 1</p> |  <p>3556 <i>For Use with 3558, 3587, 3588</i> Flexzilla High Flow Coupler 1/4 in. MNPT Steel/Aluminum Max Pressure: 300 psi Box Qty. 1</p> |  <p>3558 <i>For Use with 3556, 3586</i> Flexzilla High Flow Ball Swivel Plug 1/4 in. MNPT Nickel Plated Steel Max Pressure: 300 psi Box Qty. 1</p> | <p>(Empty)</p> |

S & R FASTENER CO., INC.

3571

Cyclone Blow Gun Kit
Includes: (2) 6" Extensions
(3) Needle Tips (1 in., 2 in., 3 in.)
Xtreme-Flo Nozzle
Quiet-Flo Nozzle
Rubber Tip
Tip Adapter
Box Qty. 1

The Cyclone Blow Gun features an ergonomically superior gun body for maximum comfort and control which reduces operator fatigue. A variable flow trigger regulates air flow precisely. The Cyclone delivers maximum flow, equal to or greater than the competition. The durable gun body is ideal for extreme use. Unique to the Cyclone is the modular accessory system, allowing you to customize the gun extension length and tips for a given application. Cyclone meets or exceeds OSHA standards.



4087

Flexzilla Enclosed Air Hose Reel
Economical, retractable.
Includes 3/8" x 50 ft hose and
Lead-in hose.
Box Qty. 1

FEATURES:

Auto Retract/Latch Hose Mechanism - Simplifies every job by keeping excess hose out of the work space.
Positive Latching Mechanism - Locks hose automatically in 18 in. intervals.
Durable Construction - Made from durable UV stabilized polypropylene.
Adjustable Hose Stopper - Increase or decrease the length of the hose that remains when hose is fully retracted.
Lead-in Hose Included - 3/8" x 3 ft. 1/4 in. MNPT
Swivel Mount Bracket - Pivots in the direction of your work, reel can be mounted to wall or ceiling.
Flexzilla Models - Includes Flexzilla air hose and lead-in hose.
Bend Restrictor - Prolongs the life of the air hose, featured on ZillaReel models.



4088

Flexzilla Retractable
Air Hose Reel
With Levelwind technology
- a unique winding system
that automatically layers
hose back and forth across
the reel ensuring that the
hose is coiled smoothly and
easily every time.
Includes 3/8" x 75 ft. hose &
3/8" x 5 ft. Lead-in hose.
Box Qty. 1

FEATURES:

Adjustable Hose Stopper - Increase or decrease the length of the hose that remains when hose is fully retracted.
Seven Position Locking Bracket - Reel can swivel freely on a mounting bracket up to 135° or can be locked into place using the locking brace. Up to seven different locking angles can be utilized.
Latching Mode Switch - Choose from latching hose every 3 ft. for extended use or switch to free run for immediate automatic rewinding.
Extra Large Swivel - A 3/4" swivel reduces flow restrictions and allows for maximum flow.
Free Standing Base w/Built-in Handle - Portable! Use freestanding or mounted on wall or ceiling. Flat base allows reel to rest on ground.
Durable Construction - Made from durable UV stabilized polypropylene.
Lead-in Hose Included - 3/8" x 5 ft. 1/4 in. MNPT
Flexzilla Models - Includes Flexzilla air hose and lead-in hose.



KX6-207A

TPMS Rubber Snap In Valve
80psi max cold inflation pressure
Max Speed rating 115 MPH
T-10 Screw Torque 11.5in-lbs
Box Qty. 1



KX6-234

TPMS Aluminum Clamp In Valve
115psi max cold inflation pressure
Max Speed rating 155 MPH
TPMS Nut Torque 62in.-lbs.
T-10 Screw Torque 11.5in-lbs
Box Qty. 1



KX6-124

TPMS Aluminum Valve
Service Pack
Box Qty. 1



KX34500

TPMS EZ Sensor
Dual Frequency -
315 & 433 mhz
Works w/ Snap-On, OTC, MAC,
Matco, Schrader, NAPA & Bartec
Box Qty. 1