



Urethane Clear 4:1

#AC9015-1 (1 Gallon)

A slow drying user friendly clearcoat that produces an extremely durable finish. Available in gallons and mixes 4:1 with #AH6370-4, #AH6380-4 and #AH6390-4.



Urethane Activator

Quart for use with #AC9015-1
#AH6370-4 Fast: 60° to 70°F
#AH6380-4 Medium: 70° to 80°F
#AH6390-4 Slow: 80° to 90°F



4:1 Glamour Clear 4:1


#AC9044-1 (1 Gallon)

A 4:1 version of our popular #AC9045-1, 2+1 Glamour Clear. The new favorite clear of discriminating painters for its ease to work with and the finish it provides. Available in gallons and mixes 4:1 with #AH6470-4, #AH6480-4 and #AH6490-4.



4+1 Activator

Quart for use with #AC9044-1
#AH6470-4 Fast: 60° to 70°F
#AH6480-4 Medium: 70° to 80°F
#AH6490-4 Slow: 80° to 90°F



Express Clear 4:1

#AC9035-1 (1 Gallon)

Euro clearcoat is a premium two component clear that has excellent gloss and DOI in addition to superior durability. Available in one gallon cans. Mixes 4:1 with #AH6580-4.



Urethane Catalyst

Quart for use with #AC9035-1
#AH6580-4 Medium: 70° to 80°F



Euro Gloss Clear 2:1

#AC9041-5L (5 Liter)

Euro clearcoat is a premium two component clear that has excellent gloss and DOI in addition to superior durability. Available in five liter cans. Mixes 2:1 with #AH6370-2.5, #AH6380-2.5 and #AH6390-2.5.



Urethane Catalyst

For use with AC9041-5L
#AH6370-2.5 Fast: 60° to 70°F
#AH6380-2.5 Medium: 70° to 80°F
#AH6390-2.5 Slow: 80° to 95°F



2+1 Glamour Clear 2:1

#AC9045-1 (1 Gallon)

A high solids clearcoat offering superior gloss, outstanding adhesion and excellent durability. Made from premium components. The favorite clear of discriminating painters for its ease to work with and the finish it provides. Available in gallons. Mixes 2:1 with #AH6170-4, #AH6180-4 and #AH6190-4.



2+1 Activator

Quart for use with AC9045-1
#AH6170-4 Fast: 60° to 70°F
#AH6180-4 Medium: 70° to 80°F
#AH6190-4 Slow: 80° to 90°F

For activators, select the appropriate speed depending on the temperature.



Euro Prime (Gray)

#AP8040-1 (Gray) (1 Gallon)

A premium European primer surfacer/sealer designed to be used with Euro Clear's catalysts making them universal. Available in gallons and mixes 4:1 with either #AH6270-4, #AH6280-4, or #AH6290-4.



Urethane Catalyst

Quart for use with #AP8040-1
#AH6270-4 Fast: 60° to 70° F
#AH6280-4 Medium: 70° to 80° F
#AH6290-4 Slow: 80° to 95° F



Self Etching Primer

#AP8414-1 (1 Gallon)

A two part primer that chemically protects against the corrosion process. It is recommended for protecting bare metal, galvanized steel and aluminum. #AP8414-1 provides minimal film build for maximum protection.



Self Etching Catalyst

Gallon for use with #AP8414-1
#AP8415-1 Self Etching Catalyst



Epoxy Primer (Black/Gray)

#AP8316-1 (Black) (1 Gallon)

#AP8320-1 (Gray) (1 Gallon)

A traditional Epoxy Primer offering superior flexibility and adhesion to virtually all substrates. Has excellent corrosion protection. Available in gallons and mixes 1:1 with #AP8300.



Epoxy Activator

Gallon for use with #AP8316-1 /
#AP8320-1
#AP8300-1 Epoxy Activator



Super-Fill Primer (Gray)

#AP8030-1 (Gray) (1 Gallon)

A urethane primer surfacer formulated to be applied as a high build sanding primer or a final non-danding primer-sealer. Available in gallons and mixes 4:1 with #AH6075-4 or AH6085-4.



Activator

Quart for use with #AP8030-1
#AH6075-4 Fast
#AH6085-4 Medium



**#AR2050-1 (1 Gallon) Uni-Reducer
Medium**

AR Series reducers are blended from high quality solvents and are compatible with all colored topcoats, clearcoats, and primer surfacers. Medium reducer should be used in a temperature range of 70° to 85° F. Available in gallons.



**#AR2150-1 (1 Gallon)
E-Z Blend Solvent**

Used to melt the edges of spot repairs and blend areas to produce an invisible repair. Effective and easy to use.
Available in gallons.



**#CPSX1-5 (5 Gallon)
Aqua Mask**

Aqua Mask is a water based masking agent that replaces the need to mask off with paper and tape, therefore saving time and money in the painting process. For removal, simply rinse with water and sponge or pressure wash if desired.
Available in one and five gallons.