

# Safety Data Sheet (SDS)

## Plews : High Temperature Wheel Bearing Grease

### SECTION 1: IDENTIFICATION OF THE SUBSTANCE /MIXTURE AND OF THE COMPANY /UNDERTAKING

**1.1 Product Identifier** Plews P/N: 11380, 11382, 11384, 11465

**Material Name:** Plews High Temperature Disc/Drum Wheel Bearing Grease

**Product Code:** 994 BA

### 1.2 Relevant identified uses of the substance or mixture and uses advised against

**Product Use:** Industrial grease

**Uses advised against:** This product must not be used in applications other than recommended in section 1 without taking the advice from supplier/manufacture

### 1.3 Supplier Information:

**Supplier:** Plews, Inc.  
1550 Frankling Grove Rd.  
Dixon, IL 61021

**Telephone Number:** (800) 545 - 1689

**Emergency Telephone Number:** (800) 424 - 9300

### SECTION 2: HAZARD IDENTIFICATION

#### 2.1 Classification of the substance of mixture

This material is not considered hazardous in accordance with OSHA HazCom 2012, 29 CFR 1910.1200

#### 2.2 Label elements

OSHA HCS 2012 : No significant hazard as per GHS

#### 2.3 Other hazards

**Health hazards:** Not expected to be a health hazard when used under normal conditions. Prolonged or repeated skin contact without proper cleaning may clog the skin pores resulting disorders like acne/folliculitis. Used grease may contain harmful impurities/ harmful extraneous substances.

**Safety hazard:** Not classified as flammable but will burn

**Environmental hazard:** Not classified as environmental hazard under GHS criteria

**Precautionary statements:**

**Prevention:** Wear protective gloves while handling. Wear eye and face protection. Wash hand thoroughly after handling

**Response:** If on skin, wash with plenty of soap and water. Remove contaminated cloth and wash thoroughly before use. If skin irritation occurs, get medical advice. If in eyes, wash with water for several minutes, in case of contact lenses, remove and wash with plenty water. In case of irritation, get medical attention.

**Storage:** Store the product in well-ventilated area. Keep the container straight lid upside. Do not lay down upside down or do not keep container horizontally. This product has natural tendency to squeeze oil if not kept properly.

**Disposal:** Take expert advice of local regulatory agency for disposing this product.

**Hazard not otherwise classified (HNOC):** None as classified under 29 CFR 1900.1200

### **SECTION 3: COMPOSITION / INFORMATION ON INGREDIENTS**

<b>Chemical Names</b>	<b>CAS #</b>	<b>EC/REACH #</b>	<b>% (weight)</b>	<b>Classification as per to regulation/ directive</b>	<b>Comments</b>
Hydrotreated heavy naphthenic distillates	64742-52-5	REACH Reg. # 01- 2119467170- 45-0001	80 %	OSHA HCS 2012 : None	Contains <3 % DMSO extract – carcinogen classification not applicable
Polyurea thickener and additive	Proprietary / mixture	-	20 %	None	-

*\*weight percentage may vary without any prior notice without affecting the performance and also may be due to batch to batch variations*

#### **Additional information:**

As per paragraph (i) of 29 CFR 1910.1200, formulation is considered as trade secret and specific chemical names and exact percentages of composition have been withheld. Specific chemical identity and exact percentage composition may be provided on request to health professional, employees concerned, or authorized representatives in accordance with applicable provisions of paragraph (i). However, this product contains the reaction product of isocyanate compound and amine compounds where the resultant product is not reported to possess any serious health / environmental hazard.

### **SECTION 4: FIRST AID MEASURES**

#### **4.1 Description of first aid measures**

**General information:** Not expected to be health hazard if used under normal conditions

**Inhalation:** Under normal conditions of intended use, this material is not expected to be inhalation hazard. If some symptom exist, remove to fresh air. If not breathing, give artificial respiration. Get medical attention

**Skin Contact:** Remove contaminated clothes. Flush exposed area with plenty of water followed by washing by soap, if available. If persistent irritation occurs, obtain medical attention. If product is injected into or under the skin due to any reason, the victim, regardless of size or appearance of wound, victim should be brought immediately to medical attention for emergency surgical needs. Though the initial symptoms due to high pressure injection may be minimal / absent, early surgical treatment may significantly reduce the extent of injury.

**Eye Contact:** Immediately flush with large quantities of cool water for at least 15 minutes. Get medical attention.

**Ingestion:** In general no treatment is necessary unless large quantities are swallowed, however, it's advisable to take medical attention. Do not induce vomiting unless directed by medical personnel. Do not give anything by mouth by an unconscious person.

**Self-protection for first aider:** When administering the first aid, ensure that you are wearing the appropriate personal protective equipment according to the incident, injury and surroundings.

## **SECTION 5: FIRE FIGHTING MEASURES**

### **5.1 Extinguishing Media:**

**Suitable extinguishing media:** Water Spray (fog), dry chemical, foam, or carbon dioxide, sand to extinguish flames.

**Unsuitable extinguishing media:** Water stream may splash burning liquid and spread fire.

**5.2 Special hazard arising from the substances or mixture:** Hazardous combustion product may include a complex mixture of airborne solid and liquid particulates and gases (smoke) , carbon monoxide , unidentified inorganic and organic compounds.

**5.3 Advice to firefighters:** Proper protective equipment include chemical resistant gloves to be worn, chemical resistant suit is recommended when large contact with spill product is expected. Self-contained breathing apparatus (SCBA) must be worn when approaching a fire in confined area. Select the fire fighters clothing approved by relevant standard

## **SECTION 6: ACCIDENTAL RELEASE MEASURES**

### **6.1 Personal precautions, protective equipment and emergency procedures**

Fully encapsulating, vapor protective clothing should be worn for spills and leaks with no fire. Do not touch and walk through spill area. Do not touch damaged container or spilled material unless wearing appropriate protective clothing/equipment. Ventilate the closed area.

### **6.2 Emergency procedures**

Isolate the spill / leak area in all directions for about 50 meters (150 ft) for liquids and about 25 meters (75 ft.) for solids and semi-solids. Eliminate all ignition sources (no smoking, flares, sparks / flames in close vicinity). Keep unauthorized person away and ventilate closed space before entering.

### **6.3 Environmental procedures:**

Use appropriate measures for containment of spilled material to the environment. Prevent from entering/ spreading to drain, water, river, ditches by using sand, earth, floor dryers or other appropriate barriers.

#### 6.4 Methods and materials for containment and cleaning up

Shovel into suitable properly marked container for disposal or reclamation in accordance with local regulations.

#### 6.5 Reference to other sections

Refer to section 8 – exposure control / personal protection and section 13- disposal considerations

### **SECTION 7: HANDLING AND STORAGE**

#### 7.1 General Precautions

Store in well-ventilated area in case of risk of vapor inhalation. Use the information in this data sheet as input for risk management arising due to local conditions which help to manage safe handling of this product.

#### 7.2 Precautions for safe handling

Avoid prolonged and repeated contact with skin. Avoid inhaling the vapors/mist. When handling the drums, kegs, pails etc., proper safety shoes, and other protective clothes, safety glasses etc. should be worn. Dispose appropriately any contaminated rags/material as per prevailing local allowable practices. Keep containers in closely tight and, cool and well ventilated areas.

#### 7.3 Conditions for safe storage, including any incompatibilities

Keep containers tightly close, well-ventilated areas but covered, avoiding contact with rain or other water ingress possibilities. Keep the storage place cool preferably <120 °F / <50 °C. Higher temperature may create pressure buildup inside container and chances of container busting or leakage may occur under aggravated conditions. Keep away from other oxidizing and incompatible materials.

#### 7.4 Specific End Use (s):

This material should not be used for any other purpose than the intended use as per section 1 without the expert advice.

### **SECTION 8: EXPOSURE CONTROLS / PERSONAL PROTECTION**

#### 8.1 Control parameters

Material	Source	Type	ppm	mg/m3	Notation
Mineral oil mist	ACGIH	TWA(inhalable fraction)		5 mg/m3	

#### Additional information:

Due to semi-solid nature of the product, generation of mist and dusts is unlikely to occur

#### Biological exposure index (BEI):

No biological limit allocated

**PNEC related information:**

Data not available

**Monitoring methods:**

Monitoring of the concentration of substances in the breathing zone of workers or in general workplace may be required to confirm the compliance with local governing authority.

**8.2 Engineering measures/controls**

Adequate ventilation systems may be needed to control concentrations of airborne contaminants above permissible threshold applicable limits.

**8.3 Personal protective equipment pictograms**

**Respiratory:** In case of insufficient ventilation, use suitable respiratory equipment

**Eye/Face:** Wear safety goggles

**Skin/Body:** Wear safety shoes and protective gloves

**8.4 Environmental Exposure controls**

Minimize release to the environment. Follow best practices for site management and disposal of waste as per local regulations

**SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES**

**Information on physical and chemical properties Material description**

Appearance	Semi-solid
Color	Blue
Odor	Slight hydrocarbon
Odor threshold	Data not available
<b>General properties</b>	
Boiling point	No data available
pH	Not applicable
Specific gravity (15 °C)	0.87, 7.506 (lbs/gal)
Flash point, COC, °F/°C	400 / 204
Upper/lower flammability limits	No data available
Auto-ignition temperature	No data available
Flammability	No data available
VOC, % wt., ASTM D-972	1
Vapor pressure @ ambient temp.	< 0.13 kPa (< 1 mm Hg)
Vapor density (air =1)	< 1
Explosive properties	Not classified
Oxidizing properties	No data available
<b>Other Information</b>	
Electrical conductivity	Though no data available, this material is not expected to be a static accumulator

**SECTION 10: STABILITY AND REACTIVITY**

<b>10.1 Reactivity :</b>	No reactivity is expected under normal conditions of intended use. However, under high temperature or adverse operating conditions thermal / chemical decomposition of the product may be possible
<b>10.2 Chemical Stability :</b>	No hazardous reaction is expected under normal conditions of temperature and pressure
<b>10.3 Possibility of hazardous reactions</b>	Hazardous polymerization is not expected. Reacts with strong oxidizing agents.
<b>10.4 Conditions to avoid</b>	Extreme temperature and direct sunlight / heat / flame
<b>10.5 incompatible materials</b>	Strong oxidizing agents
<b>10.6 hazardous decomposition products</b>	Hazardous decomposition is not expected to form under normal conditions of storage

**SECTION 11: TOXICOLOGICAL INFORMATION****11.1 Information on toxicological effects**

<b>Basis of assessment</b>	Information given hereby is based on the components and the toxicology of similar products and the data indicated here are representative of the product as whole rather than for individual components
<b>Acute oral toxicity</b>	The product does not have to be classified. Test data not available. Ingestion of large quantities may cause discomfort
<b>Acute dermal toxicity</b>	The product does not have to be classified. Test data not

	available
<b>Acute inhalation toxicity</b>	The product does not have to be classified. Test data not available
<b>Skin corrosion / irritation</b>	The product does not have to be classified. Test data not available. Degreases the skin. Long term exposure may cause irritation and possible infection.
<b>Serious eye damage /irritation</b>	The product does not have to be classified. Test data not available. Temporary irritation possible.
<b>Respiratory /skin sensitization</b>	Not determined. May cause sensitization by skin contact . Symptoms may include redness, swelling , blistering , ulceration though often develop slowly
<b>Aspiration hazard</b>	Not expected to be aspiration hazard
<b>Germ cell mutagenicity</b>	The product does not have to be classified . Test data not available
<b>Carcinogenicity</b>	The product does not have to be classified . Test data not available

## 11.2 Material

## Carcinogenicity Classification

Highly refined mineral oil ( IP 346 < 3 % )	ACGIH group A4 ; not classified as human carcinogen
	IARC 3 ; not classified as to carcinogen to humans
	GHS / CLP , no carcinogenicity classification

This material is not known to contain any chemical listed as a carcinogen or suspected carcinogen by OSHA Hazard Communication Standard 29CFR 1910.1200, IARC, or the National Toxicology Program (NTP) at a concentration greater than 0.1%.

## **SECTION 12: ECOLOGICAL INFORMATION**

<b>Basis of assessment</b>	Eco-toxicological data has not been determined specifically on this product. The information given herewith are based on the information given on eco-toxicity of components and/or on similar products. the information given here are representative of the product as whole and not as individual components
<b>12.1 Toxicity</b>	Sparingly soluble mixture in aqueous media. Not toxic to fish but may coat gill structure and cause suffocation if spilled. This product may cause gastrointestinal distress in birds and mammals through ingestion.
<b>12.2 Persistence and degradability</b>	Expected to be not readily biodegradable. The major oil component expected to biodegrade over period of 100-120 days in aerobic environment at temperature above 70 F (21 °C), however finished product contain component that may persist in the environment.
<b>12.3 Bioaccumulative potential</b>	May contain component that bioaccumulate
<b>12.4 Mobility in soil</b>	Product is semi-solid in nature in most conditions and may absorb to soil and may not be mobile. It floats on water
<b>12.5 other adverse effects</b>	Product contain the components that have been classified non-volatile in nature and therefore not expected to release to environment in significant quantities.

## **SECTION 13: DISPOSAL INFORMATION**

Disposal recommendation are based on material as supplied . Disposal must be in accordance with current applicable laws and regulations, and material at the time of disposal which may vary at the time of disposal.

### **13.1 Waste treatment methods**

<b>Product disposal</b>	Try to minimize the product waste by using best applicable practices. It is the responsibility of the waste generator to evaluate the waste classification and appropriate disposal methodology in accordance with the applicable regulation. Do not dispose in to environment, in drain or in river / ponds / water reservoirs.
<b>Regulatory Disposal Information</b>	The unused product , to our information , is not listed by EPA as a hazardous waste ( 40 CFR , Part 261 D ) and also not formulated specifically to contain reactant materials which listed as hazardous waste . However used product may be regulated .
<b>Container disposal</b>	Empty container may contain residues and may be dangerous. Do not attempt to refill and clean containers without proper instructions. Empty containers should be completely drained and safely stored until appropriately reconditioned or disposed. .

## **SECTION 14: TRANSPORT INFORMATION**

	<b>Bulk shipping</b>	<b>Non-bulk shipping</b>	<b>Identification #</b>	<b>Hazardous class</b>
US DOT	Not required	Not required	Not required	Not required
Canadian TDG	Not required	Not required	Not required	Not required
European	Not required	Not required	Not required	Not required
ADR, IMDG, IATA-DGR	Not classified as hazardous product for land, sea and air transport			

## **SECTION 15: REGULATORY INFORMATION**

**OSHA Hazard Communication Standard:** This material is not considered hazardous in accordance with OSHA HAzCom 2012, 29 CFR 1910.1200.

**US Inventory list:** All components are listed or exempted (TSCA 8b)

**SARA (302/304):** No products were found

**SARA (311/312):** None

**Classification:** Immediate (acute) health hazard, delayed (chronic) health hazard

**SARA (313) Toxic Release Inventory:** This material contains no chemicals subject to the supplier notification requirements of the SARA 313 Toxic Release Program



Listed or exempt from listing /notification on following chemical inventories : AICS, IECSC, TSCA

Inventory	Status
KECI	Restrictions apply
NDSL	Restrictions apply

## **SECTION 16: OTHER INFORMATION**

This safety data sheet contains the following revisions:

**Revision Date:** June 2, 2015

**Supersedes:** December 10, 2014

*Plews, Inc. believes that the information and recommendations given hereby is based reported information based on the components and of similar products. The data indicated here are representative of the product as whole rather than for individual components. No warranty of fitness, warranty of merchantability or any other warranty, expressed or implied, is made concerning the information provided herein. The information provided herein relates only to the specific product designated and may not be valid where such product is used in combination with any other materials or process. Further, since the conditions and methods of use of this product and of the information referred to herein are beyond the control of Plews, Inc., Plews, Inc. expressly disclaims any and all liability as to any results obtained or arising from any use of the product or reliance on such information.*