Safety Data Sheet

Issue Date: 01-Jun-2004 Revision Date: 28-Mar-2014 Version 1

1. IDENTIFICATION

Product Identifier

Product Name 8010 Epoxyflex Inter-Mix 5 Resin

Other means of identification

SDS # IES-FO8010R

Recommended use of the chemical and restrictions on use

Recommended Use Repair Adhesive/Surfacer.

Details of the supplier of the safety data sheet

Supplier Address

International Epoxies & Sealers 30241 Commerce Drive San Antonio, FL 33576

Emergency Telephone Number

Company Phone Number

1-800-451-7206

Emergency Telephone (24 hr) INFOTRAC 1-352-323-3500 (International)

1-800-535-5053 (North America)

2. HAZARDS IDENTIFICATION

Appearance Thick black paste Physical State Paste Odor Faint epoxy odor

Classification

Skin corrosion/irritation	Category 2
Serious eye damage/eye irritation	Category 2
Skin sensitization	Category 1
Carcinogenicity	Category 2

Signal Word Warning

Hazard Statements

Causes skin irritation
Causes serious eye irritation
May cause an allergic skin reaction
Suspected of causing cancer



Precautionary Statements - Prevention

Obtain special instructions before use

Do not handle until all safety precautions have been read and understood

Use personal protective equipment as required

Wash face, hands and any exposed skin thoroughly after handling

Avoid breathing dust/fume/gas/mist/vapors/spray

Contaminated work clothing should not be allowed out of the workplace

Wear protective gloves/protective clothing/eye protection/face protection

Precautionary Statements - Response

If exposed or concerned: Get medical advice/attention

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

Get medical attention

IF ON SKIN: Wash with plenty of soap and water Take off contaminated clothing and wash it before reuse

If skin irritation or rash occurs: Get medical advice/attention

Precautionary Statements - Storage

Store locked up

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Other Hazards

Toxic to aquatic life with long lasting effects

Unknown Acute Toxicity

56% of the mixture consists of ingredient(s) of unknown toxicity

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS No	Weight-%
Talc	14807-96-6	40-60
Bisphenol A Diglycidyl Ether	25068-38-6	40-60
Carbon Black	1333-86-4	0-1

^{**}If Chemical Name/CAS No is "proprietary" and/or Weight-% is listed as a range, the specific chemical identity and/or percentage of composition has been withheld as a trade secret.**

4. FIRST-AID MEASURES

First Aid Measures

General Advice Provide this SDS to medical personnel for treatment.

Eye Contact Rinse cautiously with water for several minutes. Remove contact lenses, if present and

easy to do. Continue rinsing. Get medical attention.

Skin Contact Wash off immediately with soap and plenty of water while removing all contaminated

clothes and shoes. If skin irritation or rash occurs: Get medical advice/attention.

Inhalation Remove exposed individual(s) to fresh air for 20 minutes. Consult a physician / poison

center if individual's condition declines or if symptoms persist.

Ingestion Clean mouth with water and drink afterwards plenty of water.

Most important symptoms and effects

Symptoms Eye, skin, and/or respiratory irritation. Exposed individuals may experience eye tearing,

redness and discomfort. Will cause gastrointestinal tract irritation.

Indication of any immediate medical attention and special treatment needed

Notes to Physician Treat symptomatically.

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

CO2, dry chemical, foam and water fog.

Unsuitable Extinguishing Media Not determined.

Specific Hazards Arising from the Chemical

Product is not flammable.

Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal Precautions Wear protective clothing as described in Section 8 of this safety data sheet.

Environmental Precautions Prevent entry into waterways, sewers, basements or confined areas. See Section 12 for

additional Ecological Information.

Methods and material for containment and cleaning up

Methods for Containment Prevent further leakage or spillage if safe to do so. Contain with inert material.

Methods for Clean-UpSoak up with inert absorbent material. Place in appropriate containers for disposal. Discard

any product, residue, disposable container or liner in full compliance with federal, state, and

local regulations.

7. HANDLING AND STORAGE

Precautions for safe handling

Advice on Safe Handling Obtain special instructions before use. Do not handle until all safety precautions have been

read and understood. Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin, eyes or clothing. Keep out of the reach of children. Use personal protection recommended in Section 8. Wash face, hands, and any exposed skin thoroughly after handling. Avoid breathing dust/fume/gas/mist/vapors/spray. Contaminated

work clothing should not be allowed out of the workplace.

Conditions for safe storage, including any incompatibilities

Storage Conditions Keep container tightly closed and store in a cool, dry and well-ventilated place. Keep locked

up and out of reach of children.

Incompatible Materials Acids, Amines, Mercaptans, Strong oxidizing agents.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Exposure Guidelines

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Talc 14807-96-6	TWA: 2 mg/m ³ particulate matter containing no asbestos and <1%		IDLH: 1000 mg/m ³ TWA: 2 mg/m ³ containing no
	crystalline silica, respirable fraction	silica, containing no Asbestos TWA: 20 mppcf if 1% Quartz or more, use Quartz limit	Asbestos and <1% Quartz respirable dust
Carbon Black 1333-86-4	TWA: 3 mg/m³ inhalable fraction		IDLH: 1750 mg/m³ TWA: 3.5 mg/m³ TWA: 0.1 mg/m³ Carbon black in presence of Polycyclic aromatic hydrocarbons PAH
Quartz 14808-60-7	TWA: 0.025 mg/m³ respirable fraction	 (vacated) TWA: 0.1 mg/m³ respirable dust (30)/(%SiO2 + 2) mg/m³ TWA total dust (250)/(%SiO2 + 5) mppcf TWA respirable fraction (10)/(%SiO2 + 2) mg/m³ TWA respirable fraction 	IDLH: 50 mg/m³ respirable dust TWA: 0.05 mg/m³ respirable dust

Appropriate engineering controls

Engineering Controls Mechanical ventilation or local exhaust ventilation is recommended.

Individual protection measures, such as personal protective equipment

Eye/Face Protection Goggles.

Skin and Body Protection Solvent resistant gloves. Wear suitable protective clothing.

Respiratory ProtectionWear an appropriate NIOSH/MSHA approved respirator if ventilation is inadequate.

General Hygiene Considerations Avoid contact with skin, eyes and clothing. After handling this product, wash hands before

eating, drinking, or smoking. If contact occurs, remove contaminated clothing. If needed, take first aid action shown on section 4 of this SDS. Launder contaminated clothing before

reuse.

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Physical State Paste

AppearanceThick black pasteOdorFaint epoxy odorColorBlackOdor ThresholdNot determined

<u>Property</u> <u>Values</u> <u>Remarks • Method</u>

pH Not determined
Melting Point/Freezing Point Not determined
Boiling Point/Boiling Range Not determined

Flash Point > 93.33 °C / > 200 °F

Evaporation Rate Not determined Flammability (Solid, Gas) Not determined Upper Flammability Limits Not determined Lower Flammability Limit Not determined Vapor Pressure Not determined Not determined Not determined Not determined Not determined

Specific Gravity 1.57 (1=Water)

Water Solubility Insoluble in water

Solubility in other solvents Not determined **Partition Coefficient** Not determined **Auto-ignition Temperature** Not determined **Decomposition Temperature** Not determined Kinematic Viscosity Not determined **Dynamic Viscosity** Not determined **Explosive Properties** Not determined **Oxidizing Properties** Not determined **VOC Content** 0%

10. STABILITY AND REACTIVITY

Reactivity

Not reactive under normal conditions.

Chemical Stability

Stable under recommended storage conditions.

Possibility of Hazardous Reactions

None under normal processing.

Hazardous Polymerization Hazardous polymerization does not occur.

Conditions to Avoid

Heat, flames and sparks. Keep out of reach of children.

Incompatible Materials

Acids, Amines, Mercaptans, Strong oxidizing agents.

Hazardous Decomposition Products

HES, AMINES, CO, CO2, H2S, SO2, NO2.

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Product Information

Eye Contact Causes serious eye irritation.

Skin Contact Causes skin irritation. May cause an allergic skin reaction.

Inhalation May cause irritation if inhaled.

Ingestion May cause gastrointestinal irritation, nausea, diarrhea, and vomiting.

Component Information

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
Bisphenol A Diglycidyl Ether 25068-38-6	= 11400 mg/kg (Rat)	-	-
Carbon Black 1333-86-4	> 15400 mg/kg (Rat)	> 3 g/kg (Rabbit)	-
Quartz 14808-60-7	= 500 mg/kg (Rat)	-	-

Information on physical, chemical and toxicological effects

Symptoms Please see section 4 of this SDS for symptoms.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Sensitization May cause an allergic skin reaction.

Carcinogenicity Suspected of causing cancer.

Chemical Name	ACGIH	IARC	NTP	OSHA
Talc 14807-96-6		Group 3		
Carbon Black 1333-86-4	A3	Group 2B		X

ACGIH (American Conference of Governmental Industrial Hygienists)

A2 - Suspected Human Carcinogen

A3 - Animal Carcinogen
IARC (International Agency for Research on Cancer)

Group 1 - Carcinogenic to Humans Group 2B - Possibly Carcinogenic to Humans

Group 3 IARC components are "not classifiable as human carcinogens"

NTP (National Toxicology Program)

Known - Known Carcinogen

OSHA (Occupational Safety and Health Administration of the US Department of Labor)

X - Present

Numerical measures of toxicity

Not determined

Unknown Acute Toxicity 56% of the mixture consists of ingredient(s) of unknown toxicity.

12. ECOLOGICAL INFORMATION

Ecotoxicity

Toxic to aquatic life with long lasting effects.

Component Information

Chemical Name	Algae/aquatic plants	Fish	Toxicity to	Crustacea
			microorganisms	
Talc		100: 96 h Brachydanio rerio		
14807-96-6		g/L LC50 semi-static		
Carbon Black				5600: 24 h Daphnia magna
1333-86-4				mg/L EC50

Persistence/Degradability

Not determined.

Bioaccumulation

Not determined.

Mobility

Not determined

Other Adverse Effects

Not determined

13. DISPOSAL CONSIDERATIONS

Waste Treatment Methods

Disposal of Wastes Disposal should be in accordance with applicable regional, national and local laws and

regulations.

Contaminated Packaging Disposal should be in accordance with applicable regional, national and local laws and

regulations.

14. TRANSPORT INFORMATION

Note Please see current shipping paper for most up to date shipping information, including

exemptions and special circumstances.

DOT Not regulated

IATA Not regulated

IMDG

Marine Pollutant This material may meet the definition of a marine pollutant

15. REGULATORY INFORMATION

International Inventories

Not determined

Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances

ENCS - Japan Existing and New Chemical Substances

IECSC - China Inventory of Existing Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

US Federal Regulations

SARA 313

Not determined

US State Regulations

California Proposition 65

This product contains the following Proposition 65 chemicals.

Chemical Name	California Proposition 65	
Carbon Black - 1333-86-4	Carcinogen	
Quartz - 14808-60-7	Carcinogen	

U.S. State Right-to-Know Regulations

Chemical Name	New Jersey	Massachusetts	Pennsylvania
Talc 14807-96-6	Х	X	X
Carbon Black 1333-86-4	Х	Х	X
Quartz 14808-60-7	Х	Х	X

16. OTHER INFORMATION

NFPAHealth Hazards
Not determinedFlammability
Not determinedInstability
Not determinedSpecial Hazards
Not determinedHMISHealth Hazards
2Flammability
1Physical Hazards
0Personal Protection
Not determined

Issue Date:01-Jun-2004Revision Date:28-Mar-2014Revision Note:New format

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet